

ZEPTEEN 20GL

Version 4.0 Revision Date 02/17/2020 Print Date 02/16/2021

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name ZEPTEEN 20GL

Material number 000000000000043250

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone 404-352-1680

Emergency telephone numbers

For SDS Information Compliance Services 1-877-428-9937

For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded

CHEMTREC: 800-424-9300 - All Calls Recorded. For a Transportation

In the District of Columbia 202-483-7616 **Emergency**

Recommended use of the chemical and restrictions on use

Recommended use : Degreaser

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid	
Colour	clear, amber, brown	
Odour	solvent-like	

GHS Classification

Flammable liquids : Category 3 Skin irritation : Category 2 Serious eye damage Category 1 Carcinogenicity Category 2

Specific target organ toxicity -

single exposure : Category 1

Aspiration hazard **GHS** label elements

Hazard pictograms







: Category 3 (Respiratory system, Central nervous system)



Signal word Danger

Hazard statements H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.



 Version 4.0
 Revision Date 02/17/2020
 Print Date 02/16/2021

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

Precautionary statements : **Prevention**:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P235 Keep cool.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components



Version 4.0 Revision Date 02/17/2020 Print Date 02/16/2021

Chemical name	CAS-No.	Concentration [%]
1,2,4-trimethylbenzene	95-63-6	>= 10 - < 30
Kerosine (petroleum), hydrodesulfurized	64742-81-0	>= 10 - < 30
Aromatic Hydrocarbons (C9 - C10)	0-00-0	>= 10 - < 30
Fatty acids, tall-oil, potassium salts	61790-44-1	>= 5 - < 10
Alcohols, C12-16, ethoxylated	68551-12-2	>= 5 - < 10
3-ethyltoluene	620-14-4	>= 5 - < 10
Alcohols, C9-11, ethoxylated	68439-46-3	>= 5 - < 10
mesitylene	108-67-8	>= 1 - < 5
4-ethyltoluene	622-96-8	>= 1 - < 5
1,2,3-trimethylbenzene	526-73-8	>= 1 - < 5
propylbenzene	103-65-1	>= 1 - < 5
2-ethyltoluene	611-14-3	>= 1 - < 5
xylenes	1330-20-7	>= 1 - < 5
cumene	98-82-8	>= 0.1 - < 1
ethylbenzene	100-41-4	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

Keep eye wide open while rinsing.

If swallowed : Keep respiratory tract clear.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

: Effects are dependent on exposure (dose, concentration,

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

contact time).

delayed

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.



ZEPTEEN 20GL

Version 4.0 Revision Date 02/17/2020 Print Date 02/16/2021

Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat. May be fatal if swallowed and enters airways.

Causes skin irritation.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,



Version 4.0 Revision Date 02/17/2020 Print Date 02/16/2021

vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline

materials.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m3	NIOSH REL
mesitylene	108-67-8	TWA	25 ppm 125 mg/m3	NIOSH REL
		TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
		PEL	25 ppm 125 mg/m3	CAL PEL
1,2,3-trimethylbenzene	526-73-8	TWA	25 ppm 125 mg/m3	NIOSH REL
xylenes	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	CAL PEL
		С	300 ppm	CAL PEL



ZEPTEEN 20GL

Version 4.0	Revision Date 02/17/2020	Print Date 02/16/2021
VEISIOH 4.U	REVISION Date 02/17/2020	FIIII Date 02/10/2021

		PEL	100 ppm 435 mg/m3	CAL PEL
cumene	98-82-8	TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0
		PEL	50 ppm 245 mg/m3	CAL PEL
ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		STEL	125 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
		PEL	5 ppm 22 mg/m3	CAL PEL
		STEL	30 ppm 130 mg/m3	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
ETHYLBENZENE	100-41-4	Sum of mandelic	Urine	End of shift (As	0.15.g/g creatinine	ACGIH BEI
		acid and		soon as	Creatififie	
		phenyl		possible		
		glyoxylic		after		
		acid		exposure		
				ceases)		
ETHYLBENZENE		Ethylbenzen	In end-	Not		ACGIH BEI
		е	exhaled air	critical		

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to



ZEPTEEN 20GL

Version 4.0 Revision Date 02/17/2020 Print Date 02/16/2021

the workstation location. Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear, amber, brown

Odour : solvent-like

Odour Threshold : No data available pH : Not applicable Melting point/freezing point : No data available

Boiling point : 154.44 °C Flash point : 45.0 °C

Method: closed cup

Evaporation rate : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : not determined
Relative vapour density : No data available
Density : 0.882 g/cm3

Solubility(ies)

Water solubility : emulsifiable

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : 6.3 mm2/s (20 °C)



ZEPTEEN 20GL

Version 4.0 Revision Date 02/17/2020 Print Date 02/16/2021

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat.

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

cumene 98-82-8 ethylbenzene 100-41-4

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

ethylbenzene 100-41-4

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Reasonably anticipated to be a human carcinogen

cumene 98-82-8

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 56.19 mg/l

Exposure time: 4 h



ZEPTEEN 20GL

Version 4.0 Revision Date 02/17/2020 Print Date 02/16/2021

Test atmosphere: vapour Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

Alcohols, C9-11, ethoxylated:

Acute oral toxicity : LD50 Oral Rat: 1,400 mg/kg

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION



ZEPTEEN 20GL

Revision Date 02/17/2020 Version 4.0 Print Date 02/16/2021

: Remarks: No data available

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

xylenes:

Partition coefficient: n-

octanol/water Components:

Partition coefficient: n-

octanol/water ethylbenzene:

octanol/water

Partition coefficient: n-: Pow: 3.6

Mobility in soil

No data available

Other adverse effects

No data available

Product:

40 CFR Protection of Environment; Part 82 Protection of Regulation

Stratospheric Ozone - CAA Section 602 Class I

Substances

: Pow: 3.12

Remarks This product neither contains, nor was manufactured

> with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: Not applicable

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Empty remaining contents. Contaminated packaging

> Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.



ZEPTEEN 20GL

Version 4.0 Revision Date 02/17/2020 Print Date 02/16/2021

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

UN1993, FLAMMABLE LIQUID, N.O.S., (ALIPHATIC PETROLEUM NAPHTHA), 3, III

Transportation Regulation: IATA (Cargo Air):

UN1993, Flammable liquid, n.o.s., (ALIPHATIC PETROLEUM NAPHTHA), 3, III

Transportation Regulation: IATA (Passenger Air):

This material is not classified.

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ethylene oxide	75-21-8	10	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Serious eye damage or eye irritation



Version 4.0 Revision Date 02/17/2020 Print Date 02/16/2021

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

 1,2,4-trimethylbenzene
 95-63-6
 18.1465 %

 ethylbenzene
 100-41-4
 0.3085 %

California Prop. 65



WARNING: This product can expose you to chemicals including cumene, ethylbenzene, 1,4-dioxane, ethylene oxide, which is/are known to the State of California to cause cancer, and toluene, ethylene oxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL This product contains one or more components that are listed on the

Canadian NDSL. All other components are on the Canadian DSL.

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)


SECTION 16. OTHER INFORMATION



Print Date 02/16/2021 Version 4.0 Revision Date 02/17/2020

Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	3*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms









Signal word Hazard statements Danger:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. IF exposed or concerned: Get medical advice/ attention. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Keep cool. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	4.0
Revision Date:	02/17/2020
Print Date:	02/16/2021

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes.



ZEPTEEN 20GL

Version 4.0 Revision Date 02/17/2020 Print Date 02/16/2021

This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.